



SIDE ELEVATION



REAR ELEVATION




GROUND FLOOR PLAN


PATIO




DOUBLE GLAZED FEATURE ROOFLIGHT WITH TOUGHENED SELF-CLEANING LOW E GLASS TO BS EN 1279/BS 5713
 DOUBLE UP FLAT ROOF JOISTS AND BOLT TOGETHER WITH M12 BOLTED AND DOG TOOTH CONNECTORS



SIDE ELEVATION



SECTION A



PROPOSED ROOF PLAN 1:200

NO TREES WITHIN 30M OF EXTENSION LIKELY TO AFFECT THE FOUNDATIONS



SITE LOCATION PLAN 1:1250

FLOOR ROOF
12.5mm of stone chippings bedded in bitumen compound, 3 layers of bitumen felt, top layer to be high performance felt hot laid and built up in accordance with BS 6229:2003. 150mm x 50mm C24 grade s.w. joists @ 400mm c/c. Double up joists with 12mm bolted and dog tooth connectors to trim rooflight opening.

U-value of roof to be less than 0.18W/m² K in accordance with part L. **WARM ROOF:** 150mm Celotex 1E3000/TC3000 combined insulation and decking fixed to 1:40 fall 12.5mm plasterboard and skim. Fels and mineralised felt flashing carried min 150mm up adjoining walls with code 4 lead flashing over. Provide insulated box gutter with leaded weir to existing 75mm R.W.P.

WALLS
Facing bricks to match existing on 100mm block 85mm cavity filled with drytherm insulation batts, 100mm Celcon or the malleable block U value better than 0.11W/m² K inner skin with 12mm plaster. U value to wall to be less than 0.28/m² K. in accordance with part L1B 2006. Thermobate cavity closers to openings. Cavity to remain open for 225mm below lowest dpc.
Wall ties to BS 1243 staggered 900mm horizontally and 450mm vertically doubled at openings. Tooth in new walls and maintain cavities. Vertical dpc's to all reveals. Walls parallel to timber restrained by 30mm x 5mm galv. m.s. anchor straps with noggins @ max. 2000mm c/c's engaging 3 no. joists/rafters.

FOUNDATIONS AND SLAB
450mm wide 1:3:6 mass concrete foundations min. 1000mm below ground level and to 600mm min. below any tree root activity and to invert level of adjacent drains, foundations to comply with N.H.B.C. Practice Note 4.2. 1:3 cement/sand screed on 3 coats of synthaprefe dpm continuous with dpc on 150mm concrete slab on 80mm high density Celotex GA3000Z floor insulation on 1200g polythene membrane on 150mm well consolidated hardcore. U-value of slab to be less than 0.18W/m² K. There are no trees within 30m of extension likely to affect the foundations

DRAINAGE BELOW GROUND
All new drainage to be in accordance with BS:EN 752:2008. Drains to be 110mm dia. Upvc osma drains with min. 1:40 fall. Bedded and surrounded in 100mm of pea shingle. Provide R.C. concrete lintels over any drains passing through walls or foundations and provide 75mm concrete capping to any drains less than 600mm deep. New gullies to be back inlet type. Drains to be tested on laying and on completion of works to the satisfaction of building control. New inspection chambers to be 450mm dia osma inspection chambers to a depth of 900mm and 750mm dia for depths upto 1500mm deep. Sootaways where used to be a min. 500mm from any building and to be in accordance with BRE Digest 365.

HEATING, FIREPLACES AND FLUES
Any new/extended heating system to comply fully with the Domestic Building Services Compliance Guide 2010.

WINDOWS AND VENTILATION & LIGHTING
All new double glazed windows and doors to have min. 16mm argon filled air gap with low E glass providing a u-value less than 1.6 w/m² k.

All new glazing in critical areas to be in toughened glass to BS:EN 1279/BS 5713 compliant in accordance with part N. Windows to provide 5% openings to habitable rooms. 8000mm² net glazing area with low e.

New internal lighting to comply with table 40 of the Domestic Building Services Compliance Guide 2010 (75% of new light fittings.) All new double glazed windows and doors should be provided with draught seals to prevent unwanted air infiltration

LINTELS
Catric Cg70/100 to openings up to 1800mm Cx70/100 to wider openings. Min. 150mm end bearings.

ELECTRICAL
All Electrical work required to meet the requirements of Part P (Electrical Safety) and BS7671 and IEE Regulations (17th Edition) and must be designed, installed, inspected and tested by a person competent to do so. Prior to completion the council must be satisfied that the appropriate electrical installation certificate has been issued for the work, and has been signed by a person competent to do so. New fixed lighting to be low energy type.

GENERAL
All work to be carried out in accordance with the Building Regulations 2010 and as amended and current B.S Codes of Practice. Adequacy of existing walls, lintels and foundations to be checked on site prior to loading. All dimensions must be checked on site. Any discrepancy in dimensions must be notified before proceeding. No responsibility will be accepted for alterations carried out without notification. Materials and workmanship are to be to the satisfaction of the client matching existing where possible. Where applicable consent from the adjoining owner should be sought under the provisions of the party wall etc. act 1996. All new electrical fittings, radiator positions etc are to be agreed on site with client. The builder is to remove all debris as it accumulates and on completion leave the site tidy to the clients satisfaction.

<p>2 MULBERRY MEAD HATFIELD HERTFORDSHIRE AL10 9EN PROPOSED SINGLE STOREY REAR EXTENSION SCALE 1:50 1:100 1:200 1:1250 DATE : NOVEMBER 2013 DRAWING NO. 04 DRAWING SIZE A1</p>
<p>CLIENT DR I WAHEED NEIL ANDERSON PLANNING & BUILDING DESIGN SERVICES 1A WOODLAND WAY OAKLANDS WELWYN HERTFORDSHIRE AL6 0RZ TEL. 01438 717854</p>