

Cambrian Slates embody the beauty and character of natural slate. Made in Wales from over 60% recycled Welsh slate, Cambrian tops the range in both looks and performance and has a proven track record even on pitches as low as 15°. Whilst light in weight, Cambrian's unique three point fixing makes it suitable for even the most exposed sites.

- Size (overall) 300 x 336mm
- Minimum Pitch and Headlap 15° at 75mm headlap, 25° at 50mm headlap (The minimum pitch is based on a maximum rafter length of 10 metres. For rafter lengths greater than this, please contact the Technical Solutions Hotline on 08708 702595) Maximum Pitch 90°(subject to fire resistance requirements above 69°) Maximum Headlap 90mm
- Minimum Gauge/Batten Spacing 210mm Maximum Gauge/Batten Spacing below 25° 225mm 25° and over 250mm
- Hanging Length (approx.) 294mm Cover (all figures are net and do not allow for wastage) Linear cover of 1 slate 300mm
- Covering capacity at max gauge 13.3 slates/m<sup>2</sup>
- Weight (at max. gauge approx.)\* 17kg/m<sup>2</sup> per pallet, including pallet (approx.) 0.77 tonnes
- Fix using 9196 Slate Clips, 9193 Verge Clips & 9192 Eave clips
- Battens Required (at max. gauge) 4.0m/m<sup>2</sup> Batten Size Rafter centres up to 450mm 38 x 25mm Rafter centres up to 600mm 50 x 25mm

Length	300 mm
Thickness	10 mm
Width	336 mm
Weight	2.70 kg
Material	Concrete
Colour	Slate Grey
Coverage	13.3 m <sup>2</sup>
Usage	Roofing
UV Protected	Yes
Pack Quantity	10
Type	Slate
Made To Order	N
Manufacturer Model No	470130
Country Origin	UK
Brand Name	Redland
Range Description	Concrete Roof Tiles