


OLYMPUS Twin Pack - 6x4 Wide - Smooth Body RCV

Elite 6 - 6x4 Wide Track

Euro 6 SPECIFICATIONS

35/65 split shown (50/50 split also available)



Vehicle model	OLTP-22 6x4	
Compaction body type - effective volume(s)	Olympus Twin Pack-22 (21.6 m ³)	
Elite chassis type	6x4 Wide Track	
GVW (Gross Vehicle Weight)	26000	
Front axle plated weight	8000 (7100*)	
Rear axle/bogie plated weight	19000	
Recycling box type	-	
Recycling box type (capacity m ³)	-	
V1 Overall wheelbase	5300	
Turning circle - overall (metres)	19.1***	
Vehicle unladen weight**	16960	
V2 Overall length [§]	9225	
Overall length - tailgate raised [§]	10280	
V3 Front axle to front of compaction body	650	
V4 Front overhang	1665	
Front overhang - cab tilted	3465	
V5 Rear overhang	2260	
Rear overhang - tailgate raised	3120	
V6 Overall height	3690	
Overall height - tailgate raised	5190	
V7 Height at exhaust tip - nominal	3800	
V8 Cab roof height	3130	
Cab roof height - cab tilted	3690	
V9 Cab floor height	825 Driver side, 885 Passenger side	
V10 First cab step height from ground	495	
V11 Rave rail height	1070	
V12 Ground clearance at lowest part of vehicle	250	
V13 Ground clearance - tailgate	435	
V14 Approach angle	15.5°	
V15 Departure angle	15°	

(*) Optional front axle plated weight of 7100 kg with 295/80R22.5 tyres.

(**) Typical rear mounted lifting device equipment will add up to 1200 kg.

(***) Turning circle shown is for worst case, fitment of optional tyres may reduce turning circle.

(§) Excludes front view mirror which adds approx. 230 mm

NOTE: Unless otherwise stated, all dimensions are nominal, in mm and represent an unladen vehicle without a lifting device and fitted with standard tyres; tyre deflection is not included. All specifications are subject to manufacturers tolerances. An allowance of +/- 2% should be made for all dimensions. All weights are in kgs and include oil and water, and on diesel fuelled vehicles, AdBlue and 50 litres of fuel. Additional equipment may alter dimensions and weights quoted.

DENNIS EAGLE



OLYMPUS Twin Pack - 6x4 Wide - Smooth Body RCV

Elite 6 - 6x4 Wide Track

Euro 6 SPECIFICATIONS

Chassis cab

- Elite 6 6x4 Wide Track.
- Cab - Low floor with one step entry, Cromwell stainless steel construction, standard seating for driver + 3 crew, optional driver + 1 or driver + 4 seating.
- Engine - Volvo (Euro 6) D8K 280/320 bhp, 6 cylinder, 7.7 litre in-line diesel.
- Braking system - full air - twin circuit, EBS with Electronic Stability Program, Traction control (ASR), 4 wheel parking brake.
- Gearbox - Allison MD 3000, 6 speed automatic.
- Front suspension - Full air self-levelling with anti-roll bar.
- Drive axle suspension - HN460 rubber suspension as standard; Optional Electronic Levelling Control (ELC), Self-levelling air suspension with chassis raise and chassis lower functions and anti-roll bar.
- For detailed specification and options, see relevant Elite 6 Datasheet.

Body

- Constructed from high tensile steel one piece rolled side sheets and braced by front and rear hoops, with pressed integral channels and flat floor.
- Sides in 4 mm S275 EN10025, Roof in S355 EN10025.
- Floor in three sections across width: 5 mm S355 EN10025.
- Rear hoop: 5-6 mm S355 EN10025.
- Barrier rails: 8 mm DOMEX 700 (700 N/mm²).
- Rear cross-member: 6 mm DOMEX 650 (650 N/mm²).
- The body is divided longitudinally by a reinforced central partition to give two totally separate compartments with the following capacities (m³)
50/50 Width body: **A** = 10.8, **B** = 10.8
35/65 Width body: **A** = 7.5, **B** = 14.1.

Refuse Ejection Plate

- Separate ejection plates.
- Ejection plate face is manufactured from high tensile abrasion resistant steel, forming a smooth and unobstructed discharge surface.
- Pressure regulation of the ejection plate from cab display.
- Self lubricating bearings guide the ejection plate along rails within the body.
- Multi-staged double acting hydraulic cylinder enables efficient ejection and retraction.

Tailgate

- Two totally independent tailgates.
- Capacities (m³):
50/50 Width tailgate: **A** = 0.93, **B** = 0.93
35/65 Width tailgate: **A** = 0.62, **B** = 1.24.
- Low rake rail height for manual loading and versatile lifting device mounting with bolt-on rake rail adaptor for lifting devices.
- Substantial pressed side plates form integrated channels to guide the compaction mechanism.
- Hydraulic packer plate cylinders are positioned to eliminate damage from waste.
- Reduced overhang for improved weight distribution and manoeuvrability.
- Integral rear frame for lifting device mounting.
- Floor: 8 mm HARDOX 400 (400 HB- 1000 N/mm²).
- Sides: 7 mm HARDOX 400 (400 HB- 1000 N/mm²).
- Rake Rail: 4 mm HARDOX 400 (400 HB- 1000 N/mm²).
- Retainer Plate: 4 mm WELDOX 700 (700 N/mm²).

Compaction Mechanism

- Totally independent two-plate fabricated carriage plate and packer plate design.
- Manufactured using high tensile abrasion resistant steel.
- Slides within tailgate channels on low friction self lubricating bearings.
- Heavy duty carriage and packer cylinders.
- The remaining structural elements are constructed in steel S355 EN10025
- Base sheet & tube: 4 mm HARDOX 400 (1000 N/mm²).
- Packer plate base: 6 mm HARDOX 400 (1000 N/mm²).
- Nominal 18 second cycle time.

Hydraulic System

- Quiet, PTO mounted variable displacement pump with 130 cc/rev maximum flow supplying both compaction mechanism circuits.
- Lifting device circuits supplied by separate close coupled pump.
- Body mounted 200 litre tank with remote pressure fill.
- Full flow 10 micron return line filter controls contaminant levels.
- Engine speed is maintained by electronic throttle control system when hydraulic power consumption increases.
- Independent tailgate compaction mechanism control valves.
- Heavy duty inverted packer plate cylinders fitted with maintenance free spherical bearings.
- Heavy duty inverted compaction cylinders mounted outside the compaction mechanism, clear of the loading area.
- Retention barriers with adjustable pressure.

Electrical System

- Fully integrated CANbus system logic (CANopen) with integral axle load weight indication.
- Simple display unit in cab for body controls and diagnostics.
- Fully water-proofed side mounted junction box contained within a locker allowing easy access for diagnostics and maintenance via laptop.
- Number and colour coded wiring for easy identification, maintenance and fault finding.
- Weatherproof switch, plug and socket connectors.

Safety

- **CE** Approved. Safe by design.
- Circuit designed to enhance Health & Safety features, and installation of lifting devices.
- Prepared for EN 1501-1:2011 & EN 1501-5:2011.
- Two-plate design, automatic body/tailgate locks and clean discharge remove the need to approach moving parts.
- Interlocks prevent the mechanism from working unless the tailgates are fully lowered.
- Automatic gearbox interlocks enhance safe operations.
- Tailgate lift rams are fitted with integral pilot operated load holding valves so that even if a hose fails, or is removed, the tailgate cannot descend unless positively powered downwards.
- Indicator icons show the driver when the mechanism is in operation, and when the tailgates are out of their locks.
- In cab discharge controls as standard, with external tailgate lower controls for optimised safety.
- Interlocked access door for safe maintenance operations.

Options

- A range of compatible lifting devices and DIN frames are available.
- Ladder to access the side door of the body.
- Leachate tank between body and tailgate.
- Brush & shovel with mountings.
- Hand wash unit.
- Rubber packer plate flap.

Dennis Eagle Ltd. (the company) reserves the right to change the specification, design, material, procedures and dimensions of the vehicles described herein without prior notice at any time in the future, in accordance with the company's constant product improvement policy.

© Dennis Eagle Ltd. 2013

www.dennis-eagle.com

e: sales@dennis-eagle.co.uk

t: +44 (0) 1926-458500

Dennis Eagle Ltd. Heathcote Way, Heathcote Industrial Estate, Warwick CV34 6TE. UK

For more details of specifications and options please consult a Dennis Eagle Sales representative.

DENNIS EAGLE
